

## ULTRACUT Teknik Özellikleri

TIP	Kesme Açısı	K. Uzunluğu	K. Kapasitesi	Dak. Kes. Sayısı	Uzunluk	Mak. Geniřliđi	Yükseklik	Geniřlik	T. Yüksekliđi	Ayaklar Arası	Bas. Sil. Adedi	A. D. Moturu	A. D. Çal. Mesafesi	A. D. Hızı	Motor	Yađ Tankı	Ađırlık
	(°)	mm	mm	1/dak.	mm	mm	mm	mm	mm	mm	pcs	kw	mm	n	kw	lt	kg
2106	0,5°..1,5°	2100	6	15...20	3150	2050	2020	2950	790	2480	11	0.75	1000	200	11	200	5950
2110	0,5°..2,5°	2100	10	13...15	3100	2250	2220	3000	815	2480	11	0.75	1000	200	22	300	8550
2606	0,5°..1,5°	2600	6	14...19	3500	2050	2020	2950	790	2980	13	0.75	1000	200	11	200	7150
2610	0,5°..2,5°	2600	10	12...14	3600	2250	2220	3000	815	2980	13	0.75	1000	200	22	300	9450
2613	0,5°..2,5°	3100	13	10...12	3700	2250	2290	3000	815	2980	13	0.75	1000	200	22	300	11650
3106	0,5°..1,5°	3100	6	13...17	4000	2050	2020	2850	790	3480	15	0.75	1000	200	11	200	7950
3110	0,5°..2,5°	3100	10	11...15	4050	2250	2220	3000	815	3450	15	0.75	1000	200	22	300	10750
3113	0,5°..2,5°	3100	13	10...14	4050	2250	2290	3000	815	3450	15	0.75	1000	200	22	300	12250
3116	0,5°..2,5°	3100	16	7...11	4150	2450	2450	3100	880	3450	15	0.75	1000	200	30	400	18250
3120	0,5°..2,5°	3100	20	6...10	4200	2480	2700	3250	1000	3450	15	1.5	1000	200	37	500	24650
3125	0,5°..2,5°	3100	25	4...9	4200	2480	2850	3250	1000	3450	15	1.5	1000	200	45	500	29250
4106	0,5°..1,5°	4100	6	11...16	5000	2100	2080	2850	790	4480	19	0.75	1000	200	11	200	9750
4110	0,5°..2,5°	4100	10	9...14	5050	2250	2320	3000	815	4450	19	0.75	1000	200	22	300	13750
4113	0,5°..2,5°	4100	13	8...13	5050	2250	2340	3000	815	4450	19	0.75	1000	200	22	300	15450
4116	0,5°..2,5°	4100	16	6...11	5150	2350	2550	3100	880	4450	19	1.5	1000	200	30	400	23500
4120	0,5°..2,5°	6100	20	5...9	5200	2430	2890	3250	1000	6500	19	1.5	1000	200	37	500	28250
6106	0,5°..1,5°	6100	6	8...12	7100	2450	2550	2950	950	6500	32	1.5	1000	200	22	300	25350
6110	0,5°..2,5°	6100	10	8...10	7150	2450	2580	3100	1000	6500	32	1.5	1000	200	30	300	27500
6113	0,5°..2,5°	6100	13	7...10	7180	2450	2580	3100	1000	6500	32	1.5	1000	200	30	300	29500
6116	0,5°..2,5°	6100	16	4...8	7200	2550	2750	3250	1000	6500	32	1.5	1000	200	30	400	35500
6120	0,5°..2,5°	6100	20	3...6	7250	2600	3150	3350	1100	6500	32	1.5	1000	200	37	500	49650

